

***Deburr easily
with a single tool.***

***Following the surface,
missing nothing!***

Flexible deburring tool holder
BarriquanTM



Flexes 10_{mm} vertically.

Uniform finishing

Allows tool to maintain constant pressure against workpiece.
Easy adjustment of pressure depending on burr size.

Barriquan
Demonstration
Video



Amazing Features

BarriquanTM

01 Flexible movement enables uniform finishing



Not using Barriquan



using Barriquan

02 Finish even complex shapes with simple programs.



Shapes of varying heights



Lateral pipe hole

03 Attachable to Various machines.



Machining center



Robot arm

04 Attaches to Various tools



Brush type tool



Carbide rotary bar

Line Up


BC 10-20

Frontside

Capable of fine pressure adjustments



- Attaches to : Machining center
- Size : $\phi 32 \times 120L$
- Mass : 280g
- Shank size : $\phi 20 \times 40L$





BC 10-10

Frontside

Small diameter shank type



- Attaches to : Machining center
- Size : $\phi 25 \times 100L$
- Mass : 140g
- Shank size : $\phi 10 \times 35L$





BCT 10-10

Backside

Small diameter shank type



- Attaches to : Machining center
- Size : $\phi 25 \times 110L$
- Mass : 180g
- Shank size : $\phi 10 \times 35L$



CONTACT

Sugino Machine France S.A.S.

TEL: +33-1-84-17-49-87 E-mail: contact@sugino.eu

Sugino Machine Limited-Praha, Branch Office

TEL: +420-257-950-228 E-mail: info@sugino.cz

■ Specifications in this catalogue are subject to change without prior notice for further improvement. ■ Our products and other related technology (including programs) are subject to the terms and conditions of the relevant foreign trade acts depending on the nature of products or end users and their applications. All the relevant forms must be completed and submitted to the Japanese government, including the application to export technology. ■ The content of this catalogue is as of November 2018. ■ Any unauthorized use, copying or reprinting of the contents or part thereof in this catalogue is prohibited.